


FD3007 (30x30x7mm)


Product Image



Dimension Drawing



Performance Curve



Fan Performance

Allowable Ambient : Working: -20°C ~ +80°C (Ball)
Temperature Range -10°C ~ +70°C (Hydraulic)
In stock : -40°C ~ +85°C (Ball)
-20°C~+75°C (Hydraulic)

Fan Material

Outer Frame : PBT Plastic (Black) UL94V-0
Impeller : PBT Plastic (Black) UL94V-0
Bearing System : Ball / Sleeve
Leading Wire : UL1571 AWG26 + : Red - : Black
* Other requirements please consult separately.

Life Expectancy

Life Expectancy : 40°C 50, 000 hours (Ball)
40°C 30, 000 hours (Hydraulic)

Industry Application

Apply to : Charger , Power Supply , Vending
Machine , Stage lighting
equipment and so on.

Specification

Model	Rated Voltage	Voltage Range	Speed	Current	Power	Air Flow		Pressure		Noise	Curve	Weight
	VDC	VDC	RPM	Amp	W	CFM	m³/h	mm H2O	InH ₂ O	dBA	Color	g
FD3007S2U-AP00	12	6~14	12000	0.07	0.84	4.24	7.20	6.27	2.47	35.10	Black	6
FD3007S2H-AP00			10000	0.06	0.72	3.53	6.00	4.54	1.79	29.50	Red	
FD3007S2M-AP00			8000	0.05	0.60	2.79	4.74	3.09	1.22	23.80	Green	
FD3007S2L-AP00			6000	0.04	0.48	2.02	3.43	1.81	0.71	18.90	Blue	
FD3007S1U-AP00	5	3.5~5.5	12000	0.15	0.75	4.24	7.20	6.27	2.47	35.10	Black	
FD3007S1H-AP00			10000	0.12	0.60	3.53	6.00	4.54	1.79	29.50	Red	
FD3007S1M-AP00			8000	0.10	0.50	2.79	4.74	3.09	1.22	23.80	Green	
FD3007S1L-AP00			6000	0.07	0.35	2.02	3.43	1.81	0.71	18.90	Blue	

Operation direction: Clockwise as observed from the label.
Air supply direction: Side of label.
※ The above specifications are for reference and the final specifications are subject to change.